

# Finishing soap

## SOAP SOLUTION FOR SMOOTHING SEALANTS

### Advantages

- pH neutral
- For silicones, MS-polymers, acrylics and polyurethane sealants
- Causes no degradation and/or yellowing of sealants

### PRODUCT

Bostik Finishing Soap is a ready mixed neutral universal liquid for the wet tooling of sealants in joints.

### APPLICATIONS

For smoothing joints. Does not cause roughening of sealant surface or yellowing, as may occur with washing-up liquids.

### PROPERTIES

- Ready to use
- Causes no degradation and/or yellowing of sealants
- pH neutral
- Very good to use in combination with silicones, MS polymers, acrylics and polyurethane sealants
- Colourless

### HOW TO USE

Bostik Finishing Soap can be used for the wet tooling of sealants in joints. After application of the sealants the surface of the joints and the neighbouring surfaces are moistened with Bostik Finishing Soap spray. After this the joint is tooled with a spatula, a putty knife or PVC pipe. After smoothing the joint can be finished with a finger wetted with Bostik Finishing Soap. Avoid penetration of Bostik Finishing Soap between sealant and substrate to prevent possible loss of adhesion.

### TECHNICAL DESCRIPTION

<b>Application temperature</b>	+5°C and +40°C
<b>Density</b>	1,00 g/ml
<b>PH value</b>	pH=7
<b>Article code</b>	30606510
<b>Ean code</b>	8713572034268
<b>Colour</b>	Transparent
<b>Packaging</b>	500 ml, 12 pieces in a box
<b>Code</b>	30606510
<b>EAN code</b>	8713572034268

### STORAGE AND SHELF LIFE

Store unopened under dry conditions between +5°C and +40°C. Shelf life: 18 months after production.

### ADDITIONAL INFORMATION

The following publication is available upon request: Safety Information Sheet (SIS) via [bostik.sds.thewerco.com](http://bostik.sds.thewerco.com)

### BOSTIK HOTLINE

**Smart help** + 31 (0) 73 6 244 244  
+ 32 (0) 9 255 17 17



#### Bostik BV

De voerman 8  
5215 MH 's-Hertogenbosch  
T: + 31 (0)73 6244244  
[infoNL@bostik.com](mailto:infoNL@bostik.com)  
[www.bostik.nl](http://www.bostik.nl)

#### Bostik Belux SA – NV

Meulestedekaai 86  
B-9000 Gent  
T: + 32 (0) 92551717  
[info@bostik.be](mailto:info@bostik.be)  
[www.bostik.be](http://www.bostik.be)

#### Bostik SA

253, avenue du Président  
Wilson, 93211 La Plaine  
Saint-Denis Cedex France  
[www.bostik.com](http://www.bostik.com)

#### Bostik Ltd.

Common road  
ST16 3EH  
Stafford  
[www.bostik.co.uk](http://www.bostik.co.uk)